



UT380 SERIES

Illuminometers

UT381 / UT382



UT381



UT382

SPECIFICATIONS

AUTO RANGE DATA HOLD MAX MIN USB

| Specifications | Range | Best Accuracy | |
|------------------------------|-------------------|---------------|------------|
| Model | | UT381 | UT382 |
| Illuminance Measurement(LUX) | 20 Lux | ±(3.0%+20) | ±(3.0%+20) |
| | 200 Lux | ±(3.0%+8) | ±(3.0%+8) |
| | 2000 Lux | ±(3.0%+8) | ±(3.0%+8) |
| | 20000 Lux | ±(3.0%+8) | ±(3.0%+8) |
| Illuminance Measurement(FC) | 2 FC | ✓ | ✓ |
| | 20 FC | ✓ | ✓ |
| | 200 FC | ✓ | ✓ |
| | 2000 FC | ✓ | ✓ |
| Features | | | |
| Display Count | | 2000 | 2000 |
| Auto Range | | ✓ | ✓ |
| Data Hold | | ✓ | ✓ |
| Auto Power Off | Around 10 Minutes | ✓ | ✓ |
| Low Battery Indication | Around ≤7.1V | ✓ | ✓ |
| MAX Mode | | ✓ | ✓ |
| MIN Mode | | ✓ | ✓ |
| Data Storage | | 2044 | 2044 |
| USB Interface | | | ✓ |
| Auto Record Time Setup | | ✓ | ✓ |
| Real-Time Clock | | ✓ | ✓ |

GENERAL CHARACTERISTICS

| | |
|------------------------------|--|
| Power | 9V Alkaline Battery(6LF22) |
| LCD Size | 22.5mm × 32.5mm |
| Product Color | Red and Grey |
| Product Net Weight | 185 g |
| Product Size | 195mm × 45mm × 26mm |
| Standard Accessories | UT381-Battery, Carrying Bag |
| | UT382-Battery, USB Interface Cable, PC Software CD, Carrying Bag |
| Standard Individual Packing | Blister, English Manual |
| Standard Quantity Per Carton | 40 PCs |
| Standard Carton Measurement | 600mm × 450mm × 330mm(0.089 CBM Per Standard Carton) |
| Standard Carton Gross Weight | 14.3 Kg |