



■ **UT341**



■ **UT342**

SPECIFICATIONS



Specifications	Range	Best Accuracy	
Model		UT341	UT342
Iron Matrix Measurement	0µm~55µm	±3dgt	±3dgt
	56µm~1000µm	±(3.0%+1dgt)	±(3.0%+1dgt)
Aluminum Matrix Measurement	0µm~55µm		±3dgt
	56µm~1000µm		±(3.0%+1dgt)
Resolution	1µm	√	√
Features			
Maximum Display		9999	9999
Auto Power Off		√	√
Low Battery Indication		√	√
MAX/MIN		√	√
Data Storage		2000	2000
LCD Backlight		√	√
Measurement Mode	Continuous or Single Measurement	√	√
Key Mis-press Buzzer		√	√

GENERAL CHARACTERISTICS

Power	9V Battery(6LF22)
LCD Size	22mm × 22mm
Product Color	Red and Grey
Product Net Weight	144.2 g
Product Size	153mm × 110mm × 40mm
Standard Accessories	UT341-Battery, Standard Membrane Slice, Iron Matrix Slice, Carrying Bag
	UT342-Battery, Standard Membrane Slice, Iron Matrix Slice, Aluminum Matrix Slice, Carrying Bag
Standard Individual Packing	Gift Box, English Manual
Standard Quantity Per Carton	40 PCs
Standard Carton Measurement	620mm × 400mm × 245mm (0.061 CBM Per Standard Carton)
Standard Carton Gross Weight	13 Kg