



SPECIFICATIONS

AUTO RANGE USB

Specifications	Range	Best Accuracy	
Model		UT620A	UT620B
Resolution		10μΩ	1μΩ
Resistance(Ω)	120.00mΩ/5A	±(0.25%+25)	
	60.000mΩ/10A		±(0.25%+25)
	600.00mΩ/1A	±(0.25%+25)	±(0.01%+20)
	6.0000 Ω/100mA	±(0.25%+25)	±(0.01%+20)
	60.000Ω/10mA	±(0.25%+25)	±(0.01%+20)
	600.00Ω/1mA	±(0.25%+25)	±(0.1%+25)
	6.0000kΩ/100uA	±(0.75%+30)	±(0.25%+30)
Features			
LCD Counts		60000	60000
Four-Wire Measurement		✓	✓
Wire Length Measurement		✓	✓
High/Low Limit Alarm		✓	✓
Data Storage		1000	1000
USB Data Transfer		✓	✓
Manual Range		✓	✓
Display Backlight		✓	✓
Low Battery Indication		✓	✓

GENERAL CHARACTERISTICS

Power	7.4V 4000mAh Lithium Battery
LCD Size	116mm × 87.5mm
Product Color	Red and Grey
Product Net Weight	1.5 Kg
Product Size	268mm × 168mm × 60mm
Standard Accessories	Kelvin Clips(Red&Black),Power Adaptor,USB Cable,Software CD
Standard Individual Packing	Gift Box, Carrying Bag, English Manual
Standard Quantity Per Carton	5 PCs
Standard Carton Measurement	390mm × 370mm × 285mm(0.041 CBM Per Standard Carton)
Standard Carton Gross Weight	11.5 Kg
Optional Accessories	Four-Wire Test Probes(Red&Black)×1